

# **FREEDOM** Communications System Analyzer **R9000**



[DATA SHEET](#)

# Table of Contents

Operating/Display Modes . . . . .	3
General . . . . .	3
Generator (Receiver Test) . . . . .	4
Receiver (Transmitter Test) . . . . .	4
Spectrum Analyzer . . . . .	6
Modulation Input . . . . .	7
Audio Modulation Synthesizer . . . . .	7
Vector Network Analyzer . . . . .	7
Timebase . . . . .	7
Display . . . . .	7
Remote Interface (Optional Feature) . . . . .	7

## Operating/Display Modes

AM/FM Duplex Monitor and Generator  
Audio Synthesizer  
Vector Network Analyzer  
Cable Fault Locator  
Spectrum Analyzer  
Frequency Error Meter  
Power Meter  
Audio Analyzer  
Signal Strength Meter  
SINAD/Distortion Meter



## General

### Displayed Average Noise:

Level (DANL):	-140 dBm (50 $\Omega$ input termination)
Dynamic Range:	80 dB
Input Related Spurious:	-60 dBc

### Power

DC Power Requirements:	15-19 Vdc @ 8.0 A max
AC Adapter Specs:	100-240 Vac, 2.5 A max, 50-60 Hz
Battery Power:	Dual Internal Battery, individually swappable
Battery Operation:	4 hour typical with two individually swappable batteries

### MECHANICAL/ENVIRONMENTAL

Weight:	16.5 lb (7.5 kg) with no batteries, 18.5 lb (8.4 kg) with batteries
Dimensions:	12" (30.5 cm) H x 16.5" (41.9 cm) W x 5.75" (14.6 cm) D
Operating Altitude:	Up to 15,000 ft (4572 m)
Humidity	80 % maximum relative humidity
Operating Temperature:	-20 °C to 50 °C with external DC; 0 °C to 50 °C using supplied AC adapter
Storage Temperature:	Without battery: -30 °C to +80 °C; With battery: -20 °C to +50 °C
Battery Charging Temperature:	0 °C to +45 °C
Shock and Vibration Rating:	MIL-PRF-28800F, Class 3

### WARRANTY

Standard Warranty:	Two years
Three Year Service Plan:	Optional

## Generator (Receiver Test)

Frequency Range:	10 MHz to 6 GHz
Frequency Resolution:	1 Hz

### OUTPUT LEVEL GENERATE PORT

Range FM:	+0 dBm to -130 dBm
Range AM:	-7 dBm to -130 dBm
Resolution:	0.1 dB
Accuracy:	$\pm 1$ dB

### OUTPUT LEVEL RF I/O PORT

Range FM:	-30 dBm to -130 dBm
Range AM:	-36 dBm to -130 dBm
Resolution:	0.1 dB
Accuracy:	$\pm 1$ dB

### SPECTRAL PURITY

Harmonic Spurious:	-20 dBc max
Non-Harmonic Spurious:	-35 dBc max
SSB Phase Noise (10 kHz Offset):	-105 dBc/Hz max @ 500 MHz (15 °C to 35 °C)

### FM MODULATION

Deviation Accuracy:	5 % of setting
Deviation Range:	0 to 75 kHz
Deviation Resolution:	1 Hz
Pre-emphasis (selectable):	750 $\mu$ s (selectable)
Modulation Bandwidth:	0 Hz to 20 kHz

### AM MODULATION

Depth Range:	0 to 99 % (AM Depth)
Deviation Resolution:	1 %
Depth Accuracy:	1 % of setting
Modulation Bandwidth:	100 Hz to 10 kHz
Deviation Accuracy:	1 % of setting

### SSB-AM (USB or LSB) Modulation

AM Depth Range:	0 to 99 %
Depth Resolution:	1 %
Modulation Bandwidth:	300 Hz to 20 kHz

## Receiver (Transmitter Test)

Frequency Range:	10 MHz – 6 GHz
------------------	----------------

### SENSITIVITY

Narrowband FM:	2.0 $\mu$ V for 10 dB EIA SINAD
Wideband FM:	10 $\mu$ V for 10 dB EIA SINAD
AM:	10 $\mu$ V for 10 dB EIA SINAD

## RF I/O PORT

VSWR:	< 1.5
Max Power:	50 W continuous 150 W for 30 seconds (30 seconds on, 5 minutes off)

## ANTENNA PORT

Maximum Power:	0 dBm
----------------	-------

## IF FILTERS:

6.25 kHz, 12.5 kHz, 25 kHz, 50 kHz, 100 kHz, 200 kHz

## FREQUENCY ERROR MEASUREMENT

Type of Display:	Autoranging
Resolution:	1 Hz

## FM DEVIATION MEASUREMENT

Demodulation Range:	Up to $\pm 75$ kHz
Accuracy:	$\pm 5$ % plus residual FM
Frequency Response:	Selectable per the following: Low Pass Filters: 300 Hz, 3 kHz, 20 kHz High Pass Filters: 1 Hz, 300 Hz, 3 kHz

## DEMOD HARWARE CHARACTERISTICS

Demodulation Output Level:	6.25 kHz B/W: 2.56 V / 1 kHz 12.5 kHz B/W: 1.28 V / 1 kHz 25 kHz B/W: 0.64 V / 1 kHz 50 kHz B/W: 0.32 V / 1 kHz 100 kHz B/W: 1.6 V / 10 kHz 200 kHz B/W: 0.8 V / 10 kHz
Demodulation Output Amplitude Flatness:	$\pm 0.2$ dB (300 Hz to 3 kHz), 1 dB point @ 20 kHz
Demodulation Output Impedance:	100 $\Omega$ nominal

## AUDIO WEIGHTING FILTERS

Filters: none, C-Message, CCITT	none, C-Message, CCITT
De-emphasis (selectable):	750 $\mu$ s

## AM MODULATION MEASUREMENTS

Demodulation Range:	0 to 100 %
Accuracy:	$\pm 5$ % for levels below 80 %
Frequency Response:	Selectable per the following: Low Pass Filters: 300 Hz, 3 kHz, 20 kHz / High Pass Filters: 1 Hz, 300 Hz, 3 kHz
Demodulation Output Level:	0.8 V peak per 10 % AM Modulation
Demodulation Output Amplitude Flatness:	$\pm 0.2$ dB (300 Hz to 3 kHz), 1 dB point @ 20 kHz
Output Impedance:	100 $\Omega$ nominal
SSB Sideband Suppression:	> 70 dB

## RECEIVE SIGNAL STRENGTH LEVEL METER

Frequency Range:	10 MHz to 6 GHz
Accuracy:	$\pm 1$ dB
Sensitivity:	-120 dBm (Antenna Port; 6.25 kHz IF B/W)

### BROADBAND POWER METER (RF In/Out Port)

Frequency Range:	10 MHz to 6 GHz
Measurement Range:	0.1 W to 150 W
Input Impedance:	50 $\Omega$
Accuracy:	$\pm 10$ %

### SINAD METER

Accuracy:	$\pm 1$ dB @ 12 dB SINAD
Input Level:	0.1 V <sub>RMS</sub> min
Frequency Range:	300 Hz to 10 kHz
Reading Range:	0 to > 60 dB
Resolution:	0.01 dB

### DISTORTION METER

Reading Range:	0.00 % to 100 %
Distortion Accuracy:	The greater of: $\pm 0.5$ % of distortion or $\pm 10$ % of reading
Input Level:	0.1 V <sub>RMS</sub> min
Frequency Range:	300 Hz to 10 kHz
Resolution:	0.01 %

## Spectrum Analyzer

### SWEEP

Frequency Range:	10 MHz to 6 GHz
Frequency Resolution:	1 Hz
Span Accuracy:	5 %
Update Rate:	~10 times per second (depending on span)

### AMPLITUDE

Level Accuracy:	$\pm 1$ dB
Reference Level Resolution:	1 dB
Reference Level Range:	+60 to -70 dB
T/R Port Dynamic Range:	80 dB
Typical Noise Floor Performance:	-140 dBm
SSB Phase Noise (20 kHz Offset):	-105 dBc / Hz max @ 500 MHz (15 °C to 35 °C)
Harmonic Spurious (Antenna Port, No Attenuation):	-30 dBc max
Non-Harmonic Spurious (Antenna Port, No Attenuation):	-60 dBc max
Residual Spurious (Input Terminated):	-70 dBm
Markers:	Delta, Absolute, and Frequency
Number of Markers:	8
Modes:	Standard, Average, Freeze, Max Hold, and Peak Hold

## Modulation Input

Input Impedance:	> 100 k $\Omega$
Range:	$\pm 8$ Vpk
Accuracy:	5 % of full scale
Bandwidth:	0 to 20 kHz

## Audio Modulation Synthesizer

Modulation Output Level:	Tone, Standard formats (Private Line, Digital Private Line, DPL Invert), DTMF, and external inputs from both a supplied microphone and BNC connector.
Modulation Output Level:	$\pm 8$ V peak ( $\pm 16$ / BW V / kHz FM, $\pm 0.08$ V / % AM)
Amplitude Flatness:	$\pm 0.2$ dB (300 Hz to 3 kHz), 1 dB point @ 20 kHz
1 kHz Tone Distortion:	Not to exceed 1 % THD
Output Impedance:	100 $\Omega$
Microphone Input Amplitude Flatness:	$\pm 0.2$ dB (300 Hz to 3 kHz), 1 dB point @ 20 kHz

## Vector Network Analyzer

Frequency Range:	10 MHz to 6 GHz
Parameters:	S11, S21

## Timebase

Type:	GPS Disciplined OCXO
Frequency Accuracy:	25 ppb (not locked to GPS), 5 ppb (locked to GPS)

## Display

### FRONT PANEL DISPLAY

Resolution:	1280 x 800
Size:	Size: 12.1" Full Color PCAP Multi-Touch Touchscreen

### EXTERNAL DISPLAY

External Display:	DisplayPort
-------------------	-------------

### REMOTE DISPLAY

Available over Ethernet via HTML 5 capable web browser

Distribution by:

**rfe-global**

radio frequency equipment

rfe-global GmbH  
Marie-Curie-Str. 1  
26129 Oldenburg (Oldb)  
Germany

Phone: +49 441 94911 655 / Fax: +49 441 94911 659 / E-Mail: info @ rfe-global.com

**FREEDOM**

Communication Technologies

2002 Synergy Blvd, Suite 200, Kilgore, Texas 75662

Toll Free Phone: (844)-90-FREEDOM or (844)-903-7333

Phone: 903-985-8999 Fax: 903-985-8998 Email: sales@freedomcte.com

Please visit our website at [www.freedomcte.com](http://www.freedomcte.com)

08 / Freedom Communication Technologies / Communications System Analyzer R9000



Complies With  
UL 61010-1  
CSA C22.2 No. 61010-1

All trademarks indicated as such herein are trademarks of Freedom Communication Technologies® Reg. U.S. Pat. & Tm. O. All other product or service names are the property of their respective owners. © 2019 Freedom Communication Technologies. All rights reserved. Freedom Communication Technologies reserves the right to make changes in its products and specifications at any time and without notice.