

# MAS Surveillance Monitor

7504



**Just a little bit more than analyzing...**

Edition 01/2018

rfe-global GmbH

Marie-Curie-Str. 1

26129 Oldenburg (Oldb)

Tel: +49 441 36116 655

Fax: +49 441 36116 659

E-Mail: [info@rfe-global.com](mailto:info@rfe-global.com)

**rfe-global**  
radio frequency equipment

## MultiAnalyzer 的硬件支持 Surveillance Monitor

- USB 接收器同时用于分析
  - 4 个频段（每频段最大 10 MHz 带宽）或
  - 4 个单一频率或
  - 混合操作
- 频率范围从 300 到 470 MHz（特别适合于 380 - 450 MHz 在）
  - 也可根据客户的特别要求提供其他频段
- 特别针对于
  - TETRA 和/ 或 DMR (TIER I/II/III)的测量
  - 支持 MultiAnalyzer 软件
- 易于使用（即插即用）
- 便携; 适合移动测量应用
- 重量轻: < 750 g



背面



正面



用平板电脑作为移动测量演示图



# 7504 性能指标

名称	描述
频段	300 MHz – 470 MHz (optimized for 380 – 450 MHz) other frequency bands on request
	simultaneously measurement of 4 frequencies or 4 frequency bands or mixed mode
<b>一般特性</b>	
Dimensions	205 x 153 (+40) x 32 mm (W x D x H)
Weight	approx.< 750 g (incl. batteries)
Operation temperature	0 °C to +50 °C
<b>能源供应</b>	
DC voltage, external	5 V / 500mA
Internal battery	Li-Ion 15,6 Wh
Operating time	min. 90min
<b>连接</b>	
<b>RF input</b>	
Connector	2x type TNC (female)
Impedance	50 Ω
<b>DC in</b>	
Connector	1x USB-Port type B
<b>USB-Interface</b>	
Connector (Dongle)	3x USB-Port type A (only for MAS Dongle)
Connector (PC)	1x USB-Port type B (only to connect 7504 to PC)
<b>PC-先决条件</b>	
PC-Hardware (min)	Intel® Core™ i3, 4 GB Memory, 20 GB sufficient free space on the hard-drive
OS	Windows 7, Windows 8, Windows 10 (32 or 64 bit Version)
USB-port	min. 1x USB 2.0, recommended USB 3.0 to connect 7504 with PC

此数据表的图像只是图标，可能会有变更！